

# US WATERMAKER

## Clearwater Series

One of the most compact systems on the market, the **USWATERMAKER** Clearwater Series offers all the features you would expect in a high quality R.O. unit at a very competitive price!



**USWATERMAKER** utilizes a 316SS pressure regulating valve, powder coated aluminum frames, all stainless steel fittings, and glycerin filled pressure gauges. The Clearwater Series offers flexibility in installation as well. Ask how!

### **Standard equipment includes:**

- \* CAT PUMPS® 316SS Pump Head
- \* Fiberglass pressure vessel(s)
- \* Spiral wound membranes  
with three-year pro-rated warranty
- \* Complete digital electronic monitoring
- \* Remote control
- \* Automatic fresh water flush system
- \* Magnetic drive boost pump
- \* Pre-filtration

**AVAILABLE CAPACITIES: 400–1500 GPD**

**AVAILABLE VOLTAGE: 115/230VAC**

# CLEARWATER SERIES

USWATERMAKER, INC.

Production Capacity (GPD)	400/600/800	1200	1500
Raw Water Flow	2.5 GPM	3.5 GPM	4.2 GPM
Pre-Filter	2.5X10 5 Micro & 25 Micron		
Motor TEFC Close Coupled	1.5 HP	2 HP	2.5 HP
Amps	14.0/7.0	16.6/8.3	20.8/10.4
Volts	115/230	115/230	115/230
Phase	Single	Single	Single
Weight	96/103/110 Lbs	121 Lbs	134 Lbs
Frame Dimensions	12" High x 24" Wide x 14" Deep		
High Pressure Pump	CAT PUMPS® 2SF SEEL 316 Stainless Steel Pump Head		
High Pressure Control	Adjustable Pressure Regulator		
Low Pressure Control	Low Pressure Safety Switch		
Pressure Vessels	Composite		
Membranes	Seawater 2521 or 2540		
Operating Pressures	800 PSI		
Feed Pump	Composite Magnetic Drive		
Feed Pressure	2 PSI Minimum		
Raw Water Connection	¾" Hose Barb		
Waste Water Connection	¼" FNPT Port		
Product Water Connection	¼" FNPT Port		
Fresh Water Flush	Automatic ¼" FNPT Port		
Cleaning System	Closed Loop		
Remote Panel	2-11/16" High x 4-3/16" Wide x 13/16" Deep, Cat 5 Connection		

US Watermaker, Inc.  
1424 Bargeway Rd, The Dalles, OR 97058  
Phone (800) 548-4502 Fax (541) 296-3954  
info@uswatermaker.com